

RUBBER TIRE GANTRY & RAIL MOUNTED GANTRY CRANES PRODUCTS



Our RTG/RMG spreaders are designed to handle containers sized from 20 to 45 feet with ISO twistlocks. Specially designed electrical transmissions actuate the twistlock and telescopic functions. The main structure holds all components well protected from outside forces.

The twistlock gearbox runs over the centre of the unit, thereby limiting the effects of impacts of external forces. Special attention has been devoted to ensuring maximum operational availability and making maintenance as simple as possible.

- Single Energy Saver Electrical RTG/RMG (SESER & SESER+)
- Single Hydraulic RTG/RMG (SHR & SHR+)
- Twin Hydraulic RTG/RMG (THR & THR+)
- Twin Expandable Hydraulic RTG/RMG (TEHR+)
- Single Hydraulic RTG/RMG Piggyback (SHRP & SHRP+)

sfporteq.com

[CONTACT US TO DISCUSS YOUR REQUIREMENTS](mailto:customersupport@sfporteq.com)

Email: customersupport@sfporteq.com




We combine over 150 years of experience in container handling, with the newest innovations, high quality products and a committed approach to sustainable solutions.

**Designed in Sweden. Manufactured in Europe.
Trusted worldwide.**

sfPORTEQ

Single Energy Saver Electrical RTG/RMG SESER & SESER+

- sfPORTEQ RTG/RMG spreaders SESER and SESER+ are designed to handle containers sized from 20 to 45 feet with ISO twistlocks.
- The specially designed electrical transmissions actuate the twistlock and telescopic functions.
- The main structure holds all the components well protected from outer forces.
- The twistlock gearbox runs over centre, thereby limiting the effects of impacts of external forces.
- Throughout the design special attention has been given to keep availability at a maximum and maintenance as simple as possible.



[sfporteq.com](https://www.sfporteq.com)

CONTACT US TO DISCUSS YOUR REQUIREMENTS

Email: customersupport@sfporteq.com



We combine over 150 years of experience in container handling, with the newest innovations, high quality products and a committed approach to sustainable solutions.

Designed in Sweden. Manufactured in Europe.
Trusted worldwide.

sfPORTEQ

Single Energy Saver Electrical RTG/RMG SESER & SESER+

Key Features

- High lifting capacity
- Low tare weight
- Low power consumption
- Buffers on stainless steel plates
- All standard transmissions without brakes
- Access to transmissions in all telescopic positions
- Twistlocks without adjustment of mechanics or sensors
- High telescoping speed to suit yard application

Specifications	SESER	SESER+
Lifting capacity in accordance with EN 13001 evenly loaded	50 T	50 T
< 10% eccentric	50 T	50 T
Tare weight	5.6 T	6.5 T
Twistlock rotation time	< 1 s	< 1 s
Telescopic time 20 to 40 ft	20 s	20 S
Telescopic time 20 to 45 ft	N/A	25 s
Power consumption	< 4.0 kW	< 4.0 kW
Main voltage	Default 400 VAC or per request	Default 400 VAC or per request
Control voltage		
Internal	Default 24 VDC	Default 24 VDC
Crane interface	Per request	Per request

sfporteq.com

CONTACT US TO DISCUSS YOUR REQUIREMENTS

Email: customersupport@sfporteq.com

